Test Report

Report Number: 231099-10-NDS



INSTITUTE

Gregersensvej 1 DK-2630 Taastrup +45 72 20 20 00 info@teknologisk.dk www.teknologisk.dk

Page 1 of 6 Init.: JNAS/JHA Order no.: 231099 Encl.: 3

Assignor: WOODUPP A/S, Industrivej 59, DK-6760 Ribe

Item: Heavy DUPP Article No. 3520 x 2. See enclosure B for detailed sample description.

Sampling: The assignor confirms having selected the product. The product was forwarded by the

assignor and received at Danish Technological Institute on 20 January 2025.

Period: The test took place from 24 January 2025 to 31 January 2025.

Method: EN 16121:2023 - Non-domestic storage furniture - Requirements for safety, strength,

durability and stability

Test severity 1: General: hotels, homes for the elderly, kindergarten, reception areas, meeting

rooms, lounge areas, restaurants, laboratory furniture.

Additional test methods that are referred to are listed in enclosure B.

Test results: Passed.

The detailed results are shown in enclosure A.

Terms: This test was conducted accredited in accordance with international requirements (ISO/IEC

17025:2017) and in accordance with the General Terms and Conditions of Danish

Technological Institute. The test results solely apply to the tested item. This test report may be quoted in extract only if Danish Technological Institute has granted its written consent.

Place: Danish Technological Institute, Taastrup, Building and Construction

Signature: This document is only valid with a digital signature from Danish Technological Institute. The

date of issue appears from the digital signature.

Jacob Næsby Consultant





Results

Safety requirements

Test No.	Test	Result
5.2	General requirements	Passed
5.3	Holes in tubular/rigid components	N/A
5.4.1	Shear and compression points when setting up and folding	N/A
5.4.2	Shear and compression points under influence of powered mechanisms	N/A
5.4.3	Shear and compression points during use	Passed
5.5	Hinged horizontal lids	N/A
5.6	Vertical glass components	N/A

Stability

Test No.	Test	Test Method	Loading		Result
5.7.1	Doors, extension elements and flaps closed, all storage units unloaded - Units that are, or can be, adjusted to a height of 1000 mm or less		Vertical force, N	750	N/A
5.7.2	Doors, extension elements and flaps closed, all storage units unloaded - Units that are, or can be, adjusted to a height of more than 1000 mm		Vertical force, N Outward force, N	350 50	N/A
5.7.3	All storage areas unloaded and all doors, extension elements and flaps open	EN 16122, 11.4.1	-	-	N/A
5.7.4	All storage areas unloaded with overturning load	EN 16122, 11.4.2	Vertical force, N	75	N/A
5.7.5	All storage areas loaded with overturning load	EN 16122, 11.4.3	Vertical force, N		N/A
5.7.6	Doors, extension elements and flaps closed and locked	EN 16122, 11.5	Outward force, N	100	N/A
5.7.7	Dynamic stability test for units with castors	EN 16122, 11.6	-	-	N/A

231099-10-NDS Enclosure A, Page 2 of 6



Structural safety

Test No.	Test	Test Method	Loading		Result
5.8.1.1	Static load test for tops and bottoms	EN 16122, 6.2.2	Force, N	1000	N/A
			Cycles	10	
5.8.1.2	Shelf retention test - horizontal outward	EN 16122, 6.1.2	Force, N		N/A
5.8.1.3	Shelf retention test - vertical downward	EN 16122, 6.1.3	Force, N	100	N/A
5.8.1.4	Strength of shelf supports	EN 16122, 6.1.5	Cycles	10	N/A
			Mass per unit area, kg/dm² Total mass used, kg	0.65	
5.8.1.5	Vertical load on pivoted doors	EN 16122, 7.1.2	Mass, kg 30 Cycles 10		N/A
5.8.1.6	Horizontal load on pivoted doors	EN 16122, 7.1.3	Force, N Cycles	60 10	N/A
5.8.1.7	Strength of bottom-hinged flaps	EN 16122, 7.3.1	Force, N Cycles	200 10	
5.8.1.8	Strength of extension elements	EN 16122, 7.5.2	Force, N Cycles	200 10	N/A
5.8.1.9	Slam open of extension elements	EN 16122, 7.5.4	Velocity, m/s	1.3	N/A
5.8.1.10	Interlock test	EN 16122, 7.5.6	Force, N Cycles	200 h	
5.8.1.11	Test for structure and underframes	EN 16122, 6.4.1	Force, N Cycles	350 N/A 10	
5.8.1.12	Test for unit with castors or wheels	EN 16122, 6.4.3	Cycles	2000	N/A
5.8.1.13	Overload test	EN 16122, 10.1.3	Mass per unit area, kg/dm² Total mass used, kg	2.5 50	Passed
5.8.1.14	Dislodgement test	EN 16122, 10.1.4	Force, N	100	N/A
5.8.1.15	Units supported by the floor	EN 16122, 10.2	Force, N	200	N/A



Strength and durability

Requirements in accordance with EN 16121 Severity 1

Test No.	Test	Test Method	Loading		Result
6.1.1	Strength of cloth rail supports	EN 16122, 6.3.1	Mass per unit length, kg/dm Time, h	4	N/A
6.1.2	Strength of coat hooks	EN 16122, 9.1	Force per hook, N Cycles	40 10	N/A
6.1.3	Durability of pivoted doors	EN 16122, 7.1.5	Cycles	40000	N/A
6.1.4	Slam shut test of pivoted doors	EN 16122, 7.1.4	Mass, kg Cycles	3 10	N/A
6.1.5	Slam shut/open of sliding doors and horzontal roll fronts	EN 16122, 7.2.2	Mass, kg Cycles	3 10	N/A
6.1.6	Durability of sliding doors and horizontal roll fronts	EN 16122, 7.2.3	Cycles - sliding doors Cycles - roll fronts	20000	N/A
6.1.7	Durability of flaps	EN 16122, 7.3.2	Cycles	10000	N/A
6.1.8	Durability of vertical roll fronts	EN 16122, 7.4.2	Cycles	10000	N/A
6.1.9	Durability of extension elements	EN 16122, 7.5.3	Cycles - extension elements Cycles - trays	40000 20000	N/A
6.1.10	Slam shut of extension elements	EN 16122, 7.5.4	Velocity, m/s	1	N/A
6.1.11	Displacement of extension element bottoms	EN 16122, 7.5.5	Force, N Cycles	60 10	N/A
6.1.12	Strength test for locking and latching mechanisms for extension elements	EN 16122, 7.6.2	Force, N Cycles	200 10	N/A
6.1.13	Strength test for locking and latching mechanisms for doors, flaps and roll fronts	EN 16122, 7.6.3	Force, N Cycles	200 10	N/A
6.1.14	Drop test	EN 16122, 6.4.2	2 Drop height, mm		N/A
6.1.15	Deflection of shelves	EN 16122, 6.1.4	Mass per unit area, kg/dm² Total mass used, kg	1	N/A
6.1.16	Dislodgement of clothes rails	EN 16122, 6.3.2	Mass per unit length, kg/dm Total mass used, kg	5	N/A
6.1.17	Drop test for trays	EN 16122, 8.3	Drop height, mm Cycles	350 10	N/A
6.1.18	Sustained load test for trays	EN 16122, 8.2	Kg/dm² Total mass used, kg	0.65	N/A

Documentation

Test No.	Test	Result
7	Information for use	Passed

231099-10-NDS Enclosure A, Page 4 of 6



Methods

The following standard methods are used in this test report:

EN 16121:2023 - Non-domestic storage furniture - Requirements for safety, strength, durability and stability

EN 16122:2012 - Domestic and non-domestic storage furniture - Test methods for determination of strenght, durability and stability

Measurement Decision rule according to EN ISO IEC 17025:2018 clause 3.7: No account is taken of

uncertainty: measurement uncertainty when reporting numerical results.

Sample

Description of the item tested:

Model: Heavy DUPP Article No. 3520 x 2

Type: Hanger
Width: 30.1 mm
Height: 30.1 mm
Depth: 30 mm
Weight: 0.21 kg
Materials: Aluminum
Mounting: Wall mounted

Photo of the sample as received:



231099-10-NDS Enclosure B, Page 5 of 6



Additional photos



